Application No. 09/98,599 Amandment "B" dated November 18, 2005 Reply to Office Action mailed August 19, 2005

AMENDMENTS TO THE CLAIMS

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1. (Canceled).

Claim 2. (Currently Amended) [[The]] A communication method as claimed in Claim 1 comprising:

an FDD reception step for receiving a signal based on an FDD method;

a first acquisition step for acquiring information of a signal based on a TDD method from the received signal based on the FDD method; and

a first TDD reception step for receiving the signal based on the TDD method on the basis of the acquired information of the signal based on the TDD method, wherein

the first acquisition step acquires information of a synchronization channel based on the TDD method from the received signal based on the FDD method,

the first TDD reception step receives the synchronization channel on the basis of the acquired information of the synchronization channel, and

the communication method further comprises:

Application No. 09/998,599
Amendment B. dated November 18, 2005
Reply tq Office Action mailed August 19, 2005

BEST AVAILABLE COPY

a second acquisition step for acquiring information of a code of a common control channel based on the TDD method from the received synchronization channel;

an identification step for identifying the code of the common control channel on the basis of the acquired information of the code of the common control channel;

a second TDD reception step for receiving the common control channel on the basis of the identified code of the common control channel;

a third acquisition step for acquiring a code of a communication channel based on the TDD method from the received common control channel; and

a third TDD reception step for receiving the communication channel on the basis of the acquired code of the communication channel.

Claim 3. (Original) The communication method as claimed in claim 2, wherein the information of the synchronization channel includes information relating to at least one of a code, a frequency and a timing of the synchronization channel.

Claim 4. (Original) The communication method as claimed in claim 3, wherein the information relating to the timing of the synchronization channel includes at least one of information relating to a position of a signal of the synchronization channel within a frame of the signal based on the TDD method and information relating to a timing offset between the signal based on the TDD method and the signal based on the FDD method.

Application No. 09/998,599 Amendment "B" dated November 18, 2005 Reply to Office Action mailed August 19, 2005

BEST AVAILABLE COPY

Claim 5. (Original) The communication method as claimed in claim 2, wherein the first TDD reception step makes search for the synchronization channel with respect to each of codes which are possibly used for the synchronization channel to receive the synchronization channel.

Claim 6. (Original) The communication method as claimed in claim 2, wherein the first TDD reception step makes search for a signal of the synchronization channel by shifting position for the search within a frame of the signal based on the TDD method to receive the synchronization channel.

Claim 7. (Currently Amended) [[The]] A communication method as claimed in Claim 1 comprising:

an PDD reception step for receiving a signal based on an FDD method;

a first acquisition step for acquiring information of a signal based on a TDD method from the received signal based on the FDD method; and

a first IDD reception step for receiving the signal based on the TDD method on the basis of the acquired information of the signal based on the TDD method, wherein

the first acquisition step acquires information of a common control channel based on the TDD method from the received signal based on the FDD method.

the first TDD reception step receives the common control channel on the basis of the acquired information of the common control channel, and

the communication method further comprises:

Application No. 09/998,599 Amendment '15' dated November 18, 2005 Reply to Office Action mailed August 19, 2005 **BEST AVAILABLE COPY**

a second acquisition step for acquiring a code of a communication channel based on the TDD method from the received common control channel; and a second TDD reception step for receiving the communication channel on the basis of the acquired code of the communication channel.

Claim 8. (Original) The communication method as claimed in claim 7, wherein the information of the common control channel includes information relating to at least one of a code, a frequency and a timing of the common control channel.

Claim 9. (Original) The communication method as claimed in claim 8, wherein the information relating to the timing of the common control channel includes at least one of information relating to a position of a signal of the common control channel within a frame of the signal based on the TDD method and information relating to a timing offset between the signal based on the TDD method and the signal based on the FDD method.

Claim 10. (Original) The communication method as claimed in claim 7, wherein the first TDD reception step makes search for a signal of the common control channel by shifting position for the search within a frame of the signal based on the TDD method to receive the common control channel.

Claim 11 and 12. (Canceled).

Application No. 09/998,599 Amendment "D" dated November 18, 2005 Reply to Office Action (mailed August 19, 2005)

BEST AVAILABLE COPY

Claim 13. (Currently Amended) [[The]] A communication method as claimed in Glaim-12-wherein comprising:

an FDD reception step for receiving a signal based on an FDD method;

a first acquisition step for acquiring information of a signal based on a TDD method from the received signal based on the FDD method; and

a first TDD reception step for receiving the signal based on the TDD method on the basis of the acquired information of the signal based on the TDD method, wherein

the first acquisition step acquires information of a communication channel based on the TDD method from the received signal based on the FDD method.

the first TDD reception step receives the communication channel on the basis of

the information relating to the timing of the communication channel includes at least one of information relating to a position of a signal of the communication channel within a frame of the signal based on the TDD method and information relating to a timing offset between the signal based on the TDD method and the signal based on the FDD method.

Claims 14 and 15. (Canceled).

Claim 16. (Currently Amended) [[The]]A communication method as-elaimed in elaim-15-comprising:

a step for including information of a signal based on a TDD method in a signal based on an EDD method;

Application No. 09/998,599 Amendulant "B" dated November 13, 2005 Reply to Office Action mailed August 19, 2005

<u>and</u>

an FDD transmission step for transmitting the signal based on the FDD method; and
a TDD transmission step for transmitting the signal based on the TDD method, wherein
the signal based on the TDD method includes a signal of a synchronization
channel, a signal of a common control channel and a signal of a communication channel,

the information of the signal based on the TDD method includes information of [[a]] the synchronization channel based on the TDD method.

Claim 17. (Original) The communication method as claimed in claim 16, wherein the information of the synchronization channel includes information relating to at least one of a code, a frequency and a timing of the synchronization channel.

Claim 18. (Currently Amended) [[The]]A communication method as elaimed in elaim 15 comprising:

a step for including information of a signal based on a TDD method in a signal based on an FDD method;

an FDD transmission step for transmitting the signal based on the FDD method; and a TDD transmission step for transmitting the signal based on the TDD method, wherein the signal based on the TDD method includes a signal of a common control channel and a signal of a communication channel, and

the information of the signal based on the TDD method includes information of [[a]] the common control channel based on the TDD method.

Application No. 09/998,599 Amendment "B" dated November 18, 2005 Reply to Office Action resiled August 19, 2005

BEST AVAILABLE COPY

Claim 19. (Original) The communication method as claimed in claim 18, wherein the information of the common control channel includes information relating to at least one of a code, a frequency and a timing of the common control channel.

Claim 20. (Canceled).

Claim 21. (Currently Amended) [[The]]A communication method as claimed in claim 20 comprising:

a step for including information of a signal based on a TDD method in a signal based on an FDD method;

an FDD transmission step for transmitting the signal based on the FDD method; and
a TDD transmission step for transmitting the signal based on the TDD method, wherein
the signal based on the TDD method includes a signal of a communication
channel, and

the information of the communication channel signal based on the TDD method includes at least one of information relating to at least one of a code, a frequency and timing of a position of the signal of the communication channel within a frame of the signal based on the TDD method and information relating to a timing offset between the signal based on the TDD method and the signal based on the TDD method and the signal based on the FDD method.

Claims 22-27. (Canceled).

Claim 28. (New) A mobile station comprising:

Application No. 09/998,599 Amendment "B" dated November 18, 2005 Reply to Office Action mailed August 19, 2005

FDD reception means for receiving a signal based on an FDD method;

first acquisition means for acquiring information of a signal based on a TDD method from the received signal based on the FDD method; and

first TDD reception means for receiving the signal based on the TDD method on the basis of the acquired information of the signal based on the TDD method, wherein

the first acquisition means acquires information of a synchronization channel based on the TDD method from the received signal based on the FDD method,

the first TDD reception means receives the synchronization channel on the basis of the acquired information of the synchronization channel, and

the mobile station further comprises:

second acquisition means for acquiring information of a code of a common control channel based on the TDD method from the received synchronization channel,

identification means for identifying the code of the common control channel on the basis of the acquired information of the code of the common control channel;

second TDD reception means for receiving the common control channel on the basis of the identified code of the common control channel;

third acquisition means for acquiring a code of a communication channel based on the TDD method from the received common control channel; and

third TDD reception means for receiving the communication channel on the basis of the acquired code of the communication channel.

Application No. 09/998,599 Amendated "B" dated November 18, 2005 Reply to Office Action mailed August 19, 2005

Claim 29. (New) A mobile station comprising:

FDD reception means for receiving a signal based on an FDD method;

first acquisition means for acquiring information of a signal based on a TDD method from the received signal based on the FDD method; and

first TDD reception means for receiving the signal based on the TDD method on the basis of the acquired information of the signal based on the TDD method, wherein

the first acquisition means acquires information of a common control channel based on the TDD method from the received signal based on the FDD method,

of the acquired information of the common control channel, and

the mobile station further comprises:

second acquisition means for acquiring a code of a communication channel based on the TDD method from the received common control channel; and

second TDD reception means for receiving the communication channel on the basis of the acquired code of the communication channel.

Claim 30. (New) A mobile station comprising:

FDD reception means for receiving a signal based on an FDD method;

first acquisition means for acquiring information of a signal based on a TDD method from the received signal based on the FDD method; and

first TDD reception means for receiving the signal based on the TDD method on the basis of the acquired information of the signal based on the TDD method,

Application No. 09/998,599 Amendment "B" dated November 18, 2005 Reply to Office Action mailed August 19, 2005

wherein the first acquisition means acquires information of a communication channel based on the TDD method from the received signal based on the FDD method,

the first TDD reception means receives the communication channel on the basis of the acquired information of the communication channel, and

the information of the communication channel includes at least one of information relating to a position of a signal of the communication channel within a frame of the signal based on the TDD method and information relating to a timing offset between the signal based on the TDD method and the signal based on the FDD method.

Claim 31. (New) A base station comprising:

means for including information of a signal based on a TDD method in a signal based on an PDD method;

FDD transmission means for transmitting the signal based on the FDD method; and
TDD transmission means for transmitting the signal based on the TDD method,
wherein the signal based on the TDD method includes a signal of a synchronization
channel, a signal of a common control channel and a signal of a communication channel, and

the information of the signal based on the TDD method includes information of the synchronization channel.

Claim 32. (New) A base station comprising:

means for including information of a signal based on a TDD method in a signal based on an tDD method;

FDD transmission means for transmitting the signal based on the FDD method; and

Application No. 09/998,599 Amendment "13" dated November 18, 2005 Reply to Office Action mailed August 19, 2005

TDD transmission means for transmitting the signal based on the TDD method,
wherein the signal based on the TDD method includes a signal of a common control
channel and a signal of a communication channel, and

the information of the signal based on the TDD method includes information of the common control channel.

Claim 33. (Now) A base station comprising:

means for including information of a signal based on a TDD method in a signal based on an FDD method;

PDD transmission means for transmitting the signal based on the FDD method; and TDD transmission means for transmitting the signal based on the TDD method,

wherein the signal based on the TDD method includes a signal of a communication channel, and

the information of the signal based on the TDD method includes at least one of information relating to a position of the signal of the communication channel within a frame of the signal based on the TDD method and information relating to a timing offset between the signal based on the TDD method and the signal based on the FDD method.